



Talcor Super HD

Product Data Sheet

Customer benefits

- Special solids are pre-activated to increase their natural positive affinity to all metal surfaces to ensure lubrication during frequent start ups, slow speeds or heavy loads.
- Polymers ensure the lubricant will not wash out, pound out or splatter under the heaviest loads or vibration
- Bonding and cohesive properties provide superior lubricant retention in bearings
- Incorporated fluid plastisols give optimum protection and increased life to seals.
- Scientifically designed for self-sealing protection, to keep lubricant in and contamination out
- Good pumpability over a wide temperature range, can be dispensed by conventional automatic systems where required.

Applications

- General plant lubrication, ball and roller bearings, bushings, screws, chassis, slides, and ways where loads are high and speeds are low. All weather super heavy duty service for mining, cement, steel, construction and transport industry.

Note: Talcor Super HD greases are not compatible with sodium or inorganic base greases.

Product features:

Talcor Super HD is a blend of high viscosity petroleum base oil, with shear stable lithium mixed soap thickeners and fortified with special synthetic polymers.

Superior performance capabilities are provided by the precise blending of complex additives thus providing maximum protection against wear and excellent rust and oxidation inhibiting properties.

A Chevron company product

All trademarks are property owned by Chevron Intellectual Property LLC.



Product Specifications

TALCOR SUPER HD KEY PROPERTIES	RESULTS	
NLGI Grade	1	2
Thickener	Lithium Mixed Soap	Lithium Mixed Soap
Dropping Point, °C	178	191
Base Oil Viscosity @ 40°C (cSt)	680	680
Safe Operating Temperature, °C	94	102
4-Ball Weld Point DIN 51350-4 (N)	6000	6000
4-Ball Weld Point ASTM D2596 (kgf)	800	800

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Lubricants; Africa, Middle East and Pakistan.

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltexoils.com.

For more information, go to www.chevronlubricants.com